

POTENTIOMETRE PC20



Electrical Data

Nominal resistance	20	kOhm
Resistance tolerance	± 20	%
Independent linearity	± 2.5	% of meas. range
Electrical angle	315	°
Angle tolerance (electrical)	± 3	°
Temperature coefficient of the voltage divider	100	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	100	mA
Power rating P	max. 0.75	W/40°C
Min. life (electrical)	50'000	cycles

Mechanical Data

Mechanical range	320	°
Resistance tolerance (mechanical)	± 2	°
Torque	2...6	Ncm
Min. life (mechanical)	50'000	cycles
Operating temperature	-25 ... +125	°C
Storage temperature	-55 ... +125	°C
Protection class	IP67	
End-stop strength	max. 70	Ncm
Draw out force of the shaft	min. 40	N
Draw out force of the wires	min. 50	N/1 min.
Permitted torque for nut fixation	max. 75	Ncm

Insulating resistance (500 VDC, 1bar, 2s)	8	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1.5	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	50	g

PC20

Applications

- Temperature control of industrial dryer

Features

- Compact dimensions
- Elevated torque
- High temperature range
- Protection class IP67

Options

- Other nominal resistances
- Electrical angles between 30° and 315°
- Without elevated torque

Subject to change
without notice
State: 27-Oct-2005

COMPAUT
Tel: 04 50 57 07 91
Fax: 0450572145

compaut@wanadoo.fr

CO
NTELEC