



Electrical Data		
Nominal resistance	5	kOhm
Resistance tolerance	±20	%
Independent linearity	±1	% of meas. range
Electrical travel	25	mm
Repeatability	0.05	mm
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles

Mechanical Data		
Mechanical travel	25	mm
Adjusting force of the push rod	max. 3	N
Adjusting force of the push rod with return spring	max. 10	N
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +75	°C
Storage temperature	-25 ... +105	°C
Protection class	IP65	

Standards		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	700	V
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	50	g

KL250 (KL25/KLR25)

Applications

- Gas pedal

Features

- Compact dimensions
- Design flexibility
- 5 Mio. cycles
- Excellent linearity up to ±0.25%
- Very good resolution, better 0,05mm

Options

- Linearity ±0.25 %
- Nominal resistances between 1KOhm and 20KOhm
- Pass trough push rod
- Longer push rod
- Connection by wires
- Longer cable
- Tandem-ganged
- Without bushing
- With bushing M6x0.75 or M10x0.75
- With or without return spring

Subject to change
without notice
State: 11-Nov-2005

Contelec AG
Portstrasse 38
CH-2503 Biel/Bienne
Phone +41 (0)32 3665600
Telefax +41 (0)32 3665604
sales@contelec.ch

CONTELEC