

POTENTIOMETRE PL290



PL290

Applications

- Electrical servo drive
- Rehabilitation equipment

Features

- Small dimensions
- 0.5 Mio. cycles
- Very good resolution, better 0,1°
- Linearity ± 2 %

Options

- Custom shafts design
- Custom bushing design
- Other electrical angles between 20° und 270°
- Continuous rotation

| Electrical Data | | |
|--|----------|------------------|
| Nominal resistance | 1/5/10 | kOhm |
| Resistance tolerance | ± 20 | % |
| Independent linearity | ± 2 | % of meas. range |
| Electrical angle | 270 | ° |
| Temperature coefficient of the voltage divider | 50 | ppm/°C |
| Recommended wiper current | max. 1 | μ A |
| Max. wiper current in case of malfunction | 10 | mA |
| Power rating P | max. 0.5 | W/40°C |
| Min. life (electrical) | 1 Mio. | cycles |

| Mechanical Data | | |
|------------------------|--------------|--------|
| Mechanical range | 300 | ° |
| Torque | max. 1 | Ncm |
| Min. life (mechanical) | 500'000 | cycles |
| Operating temperature | -25 ... +125 | °C |
| Storage temperature | -40 ... +125 | °C |

Protection class IP50

| Standards | | |
|---|-----|------|
| Insulating resistance (500 VDC, 1bar, 2s) | 10 | GOhm |
| Dielectric strength (VAC, 50Hz, 1min, 1bar) | 1.5 | kV |
| Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz) | 10 | g |
| Shock (half sine pulse, 7 ms) | 50 | g |

Subject to change
without notice
State: 27-Oct-2005

COMPAUT
Tel: 04 50 57 07 91
Fax: 04 50 57 21 45

compaut@wanadoo.fr

CONTELEC