

POTENTIOMETRE GL60



GL60

Applications

- Door control system
- Road roller

Features

- Hollow shaft Ø 6mm
- 5 Mio. cycles
- Excellent linearity up to ±0.25%
- Very good resolution, better 0,1°

Options

- Resistance tolerance ±10%
- Special electrical angles
- Radial cable outlet
- Mechanical end-stop

Electrical Data		
Nominal resistance	5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±0.25	% of meas. range
Electrical angle	150/354	°
Repeatability	max. 0.1	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles

Mechanical Data		
Mechanical range	360	° (continuous)
Torque	max. 0.5	Ncm
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +75	°C
Storage temperature	-25 ... +105	°C
Protection class	IP63	

Standards		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 500 Hz)	10	g
Shock	50	g

Subject to change
without notice
State: 11-Nov-2005

COMPAUT
Tel: 04 50 57 07 91
Fax: 04 50 57 21 45

compaut@wanadoo.fr

CO
NTELEC